

8-28-00

A
JC886 U.S. PTO
09/648906
08/25/00

Patent Application
Docket No. 27798-101

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re patent application of: Gerald Davis Bohannon, Jr.

For. SYNTHETIC FIBER FILLED EROSION CONTROL BLANKET

BOX PATENT APPLICATION
Assistant Commissioner
for Patents
Washington, D.C. 20231

CERTIFICATE OF MAILING BY EXPRESS MAIL

"EXPRESS MAIL" Mailing Label No. EL524958033US

Date of Deposit: August 25, 2000
I hereby certify that this paper or fee is being deposited with the U.S.
Postal Service "Express Mail Post Office to Addressee" service under
37 CFR 1.10 on the date indicated above and is addressed to the Assistant
Commissioner for Patents, Washington, D.C. 20231

Type or Print Name MARVE CARR
Marve Carr
Signature

Sir

PATENT APPLICATION TRANSMITTAL LETTER

Transmitted herewith for filing, please find the following:

- X Specification, claims and abstract of the above-referenced patent application (total of 20 pages)
- X 3 sheet(s) of drawing(s) (X formal/ ___ informal).
- X Combined Declaration and Power of Attorney (signed).
- X An Assignment of the invention to: AMERICAN EXCELSIOR COMPANY
- ___ A verified statement claiming small entity status under 37 CFR 1.9 and 1.27.
- X Other (specify): Acknowledgment postcard.

The filing fee has been calculated as shown below:

	NO. FILED	NO. EXTRA	RATE	FEE
BASIC FEE				\$690
TOTAL CLAIMS	18		\$18	0
INDEPENDENT CLAIMS	2		\$78	0
MULTIPLE DEPENDENT CLAIM(S) PRESENTED			\$260	
TOTAL FEES:				\$690
Deduct one-half of fee for Small Entity				
ASSIGNMENT RECORDAL FEE			\$40	\$40
TOTAL AMOUNT DUE:				\$730

____ Please charge my Deposit Account No. 10-0447 in the amount of \$ ____.

X Check(s) in the amount of \$730 is attached. Please charge any deficiency or credit any overpayment to Deposit Account No. 10-0447.

X The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 10-0447.

X Any patent application processing fees under 37 CFR 1.17 and under 37 CFR 1.20(d).

____ The issue fee set in 37 CFR 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR 1.311(b).

X Any filing fees under 37 CFR 1.16 including fees for presentation of extra claims.



Arthur J. Brady
Registration No. 42,356

JENKENS & GILCHRIST
3200 Fountain Place
1445 Ross Avenue
Dallas, Texas 75202-2799
214/855-4182 (Direct)
214/855-4300 (Fax)

PATENT APPLICATION
DOCKET # 27798-00101

CERTIFICATE OF MAILING BY EXPRESS MAIL

"EXPRESS MAIL" Mailing Label No. EL524958033US

Date of Deposit: AUGUST 25, 2000

I hereby certify that this paper or fee is being deposited with the U.S. Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231


Signature MARYE CARR

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Title: SYNTHETIC FIBER FILLED EROSION CONTROL BLANKET

Inventor: Gerald Davis Bohannon, Jr.
No. 8 Old Stage Trail
Lake Wylie, South Carolina 29710
Citizenship: USA

BACKGROUND OF THE INVENTION

Technical Field of the Invention

The present invention relates to erosion control blankets and, more particularly, to a soil erosion control blanket having a synthetic, fibrous filler material which is

substantially non-biodegradable. The erosion control blanket of the present invention is designed to prevent soil erosion and runoff, as well as permitting the in-growth of grasses and other vegetation, while retaining a near original state and not degrading significantly over a number of years.

History of the Related Art

Erosion control blankets have established commercial acceptance and use worldwide. Erosion control blankets are articles which resemble a form of fibrous matting in which two outer layers of netting or other material are commonly used to form an envelope or covering about a fibrous interior filler layer. These blankets are commonly used to reduce soil erosion and runoff from erosion-prone areas such as highway embankments or water drainage ditches.

Several different styles of erosion control blankets or mats are commonly in use today. One particular style of blanket that does not use a netting material is set forth and shown in U.S. Patent No. 5,786,281 which is assigned to the assignee of the present invention and incorporated herein by reference. Other styles may include at least two outer netting or facing layers that are filled with a loose fibrous material. For example, one particularly effective erosion control blanket is the CURLEX or excelsior fiber blanket manufactured and sold by the American Excelsior Company of Arlington, Texas since 1964. This blanket is fabricated in elongated rectangular mat form, from

elongated, randomly intertwined wood fibers commonly referred to as excelsior. Prior art erosion control blankets and mats such as these are commonly used in conjunction with commercial or residential construction projects in an attempt to control soil loss and runoff into adjoining areas. The blankets are unrolled along the earth area to be protected against erosion, and are secured along the sides of one another and to the underlying ground area with a series of conventional ground staple members. The ground staple members may be made of steel, wood, plastic or other materials and serve to anchor the mats securely to the covered earth area. Additionally, in some applications, erosion control blankets or mats such as these may be rolled to form a sort of artificial curb or barrier at the edge of a property or construction site.

The netting and loose fiber filler construction permits blankets or mats of this kind to be fairly light in weight and also to permit the ingrowth of grasses and other vegetation into and through the blanket. The netting primarily serves to hold the loose fiber filler together while providing a large number of openings for plant ingrowth. As these blankets will frequently become a fixture in their installment site, it is often desirable to form the inner fibrous layer of the blanket of various types of biodegradable materials. By way of example, recycled paper or fiberized waste paper, wood fibers or excelsior, straw or other naturally fibrous materials such as coconut husks may be used to provide a biodegradable filler material. However, in

some erosion-prone areas such as water runoff ditches and the like, it is particularly useful to have an erosion control blanket or mat with a more substantial and permanent filling which will not significantly degrade over long periods of time.

One solution to the problem referenced above is the use of polymeric or other synthetic fibers as filler materials. Some synthetic filler materials which have been suggested include polyethylene, polypropylene or nylon fibers and blends of fibers such as these with organic or biodegradable fibers such as those noted above. Several shortcomings have been noted by end users with these blankets which include synthetic fibers in that the blankets tend to become matted down or thinner over time and tend to lose their loft or three-dimensionality. As blankets become matted down, the fibers in the filler tend to become more tightly packed, and the subsequent in-growth of grasses and other vegetation becomes increasingly difficult. Prior art attempts to resolve fiber matting problems have involved the use of multiple netting layers disposed throughout the filler material and netting which is corrugated or shaped to hold a more three-dimensional structure. However, these solutions may involve significant additional material and labor costs to produce an erosion control blanket. Moreover, synthetic/organic blended fillers tend to degrade over time much like organic-only fillers, and merely do so at a slower rate. Thus, while synthetic-only fillers for erosion control blankets have been suggested, these appear to be somewhat

wasteful of natural resources and still suffer from shortcomings in the areas of fiber resiliency and loft.

SUMMARY OF THE INVENTION

The present invention overcomes the shortcoming of the existing designs and satisfies a significant need for a durable erosion control blanket with improved loft and resiliency properties. More specifically, the erosion control blanket of the present invention addresses the need for an erosion control blanket which does not significantly degrade over a number of years and maintains a high degree of resiliency or loft when in use. In one embodiment of the present invention, the erosion control blanket has at least three layers including a top sheet, a filler material and a bottom sheet. The top and bottom sheets generally resemble an open-mesh material or netting. Many of the particular physical characteristics of the erosion control blanket are achieved through the use of a novel synthetic fiber filler material. The filler material for use in the erosion control blanket is made up of a plurality of crimped polymer fibers which form a three-dimensional matrix between the top sheet and the bottom sheet. Moreover, it is possible to form the crimped polymer fibers from post-consumer polyester fiber material such as polyethylene terephthalate (PET). Although it is to be understood that the synthetic filler is not limited to this particular material, PET is desirable in that it is

commonly used to make soda bottles and other translucent packaging containers, and is consequently readily available in post-consumer form. Thus, it is possible to achieve the desired physical and mechanical properties in the erosion control blanket of the present invention while conserving natural resources to some extent by using a readily available post-consumer polymer material.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the erosion control blanket according to the present invention may be obtained by reference to the following detailed description when taken in conjunction with the accompanying drawings wherein:

Figure 1 is a top plan view of a section of an erosion control blanket constructed in accordance with the present invention;

Figure 2 is a cut-away side view of a section of an erosion control blanket constructed in accordance with the present invention;

Figure 3 is a top perspective view of a section of an erosion control blanket constructed in accordance with the present invention; and

Figure 4 is a block diagram of steps which are carried out to produce an erosion control blanket constructed in accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will now be described more fully hereinafter with reference to the accompanying drawings in which several preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as being limited to the embodiments set forth herein. Rather, the embodiments are provided so that this disclosure is thorough and complete, and fully conveys the scope of the invention to those skilled in the art.

Referring now to Figures 1 - 3, a section of an erosion control blanket 100 constructed in accordance with the principles of the present invention is set forth and described. Note that each of the drawings have been numbered with like numbers corresponding to like parts. As best seen in Figure 2, the erosion control blanket 100 is formed of three layers of material. The first layer is a top sheet 120 of an open-meshed material of natural or synthetic fibers. The second layer is of a loose fiber filler 140 which is arranged to form a three-dimensional matrix and provides the erosion control blanket with a required amount of loft or resiliency. The third layer is a bottom sheet 160 or open-meshed material which generally resembles the top sheet 120 or first layer in construction.

Referring now to Figure 1, the top sheet 120 is seen to have a open-meshed material or netting with a high percentage of open area. In one embodiment of the

present invention, the openings 130 in this netting material are rectangular in shape with sides ranging from about 0.50 inches to about 1.00 inches in length. The netting itself may be formed of either natural or synthetic materials, and in one preferred embodiment, is of polyethylene (PE), polypropylene (PP), or other suitable polyolefin. It is particularly desirable to make the top sheet 120 or netting of a synthetic material which is both lightweight, strong, and durable enough to resist tearing or rupture of the soil erosion control blanket 100. The netting material may also include various additives, as known in the art, to improve resistance to ultraviolet (UV) radiation or to impart a particular color. By way of example only, a small amount of carbon black additive, about 0.1% to about 2.5% by weight, may be incorporated into a suitable polymer to impart both a black color and a significant amount of UV resistance into the netting material.

Although not shown in Figure 1, the bottom sheet 160 or netting of the erosion control blanket 100 in accordance with the present invention is substantially similar in construction to the top sheet 120 as shown and described. That is, the bottom sheet 160 will also have an open-meshed material with a high degree of open area and be made of very similar materials to that of the top sheet 120.

Still referring to Figures 1-3, in another embodiment of the present invention, the top sheet 120 and the bottom sheet 160 may be constructed of polymer materials

having slightly different mechanical properties. For example, as the top sheet 120 will be exposed to more direct sunlight and UV radiation than the bottom sheet, it may be desirable to use a top sheet 120 which is stronger and heavier than the bottom sheet 160. In one preferred embodiment, the top sheet 120 is formed of 600 denier, high-tensile, polypropylene material and has a weight of about 10.0 pounds/1000 square feet and a strand count of about 9.0 and about 13.0 strands/10 inches in the machine and transverse directions, respectively. The netting has rectangular openings with sides of about 0.75 inches to about 1.00 inches in length. The top sheet 120 has a break load of about 57.0 pounds/3 inches in the machine direction and about 73.0 pounds/3 inches in the transverse direction. However, in this particular embodiment, the bottom sheet 160 is formed of 600 denier, high-tensile, polypropylene material and has a weight of about 2.87 pounds/1000 square feet and a strand count of about 13.0 to about 14.0 strands/10 inches in both the machine and transverse directions. The netting has rectangular openings with sides of about 0.70 inches to about 0.80 inches in length. The bottom sheet 160 has a break load of about 29.0 pounds/3 inches in the machine direction and about 23.4 pounds/3 inches in the transverse direction.

The filler material 140 of the erosion control blanket 100 of the present invention is an arrangement of crimped polymer fibers 150 to create a three-dimensional matrix having a desired amount of loft and resiliency. Although the polymer fibers 150 may

be arranged in various ways, a randomly dispersed loose fiber fill will generally produce a blanket with sufficient loft. In one embodiment of the present invention, the polymer fibers 150 are formed of a post-consumer polyester, namely polyethylene terephthalate (PET). This particular material is commonly used to form soda bottles and other translucent packaging containers, and is readily available in post-consumer form. By way of example only, it is also possible to purchase post-consumer PET which is of a particular color, namely green, which is derived from SPRITE, 7-UP, and other citrus flavored soda bottles. The green-colored, post-consumer PET material is desirable in some applications as it provides the resulting erosion control blanket with a visually attractive green color which tends to blend in with grass and plants.

This post-consumer polyester resin may be recycled into fibers 150 to form the filler material 140 of the blanket 100 according to the present invention. These PET fibers 150 offer a high degree of loft when crimped and tend to be more resilient than other synthetic fibers. In accordance with the present invention, the PET fibers will have a denier size of about 15 to about 500. It is the inventor's belief that the post-consumer PET fibers used in the filler of the erosion control blanket of the present invention are unique in that this particular fiber has a particularly good shape memory. That is, that when a blanket 100 filled with crimped PET fiber materials is compressed and the load is subsequently removed, the crimped fibers 150 and consequently the blanket

100 will tend to spring back to its nearly all of its original dimension. Additionally, the crimped fibers 150 will tend to entangle and cling one-to-another more aggressively than uncrimped fibers do. This particular feature of crimped fibers serves to reduce the migration of fibers out of the blanket and further assures consistent blanket loft with the passage of time. Thus, it is possible to create a erosion control blanket 100 which has a higher degree of loft and is far more resilient than prior art loose fiber filler erosion control blankets.

The recycled polyester fibers 150 used as filler material in the erosion control blanket 100 of the present invention possess a unique combination of mechanical properties. It is notable that the post-consumer PET fibers have a specific gravity greater than 1.0, and do not float in water. However, many other synthetic fibers such as polyethylene, polypropylene and the like have specific gravities of less than 1.0 and will tend to float in water. This is a particularly useful characteristic of the post-consumer PET fibers in that erosion control blankets made in accordance with the present invention may be utilized in high water runoff areas including water drainage channels. Accordingly, it is easier to keep an erosion control blanket in contact with the ground when the fibers which fill the blanket do not float under hydraulic conditions. If an erosion control blanket tends to float, it will be much less effective at reducing soil loss and preventing the washing away of grass seed and other plant matter which is

intended to grow through the erosion control blanket. The fiber material may also include various additives, as known in the art, to improve resistance to ultraviolet (UV) radiation or to impart a particular color.

In one embodiment, the post-consumer PET fibers will have denier size of about 15 to about 500, and have a preferred denier size of about 350 to about 450. The post-consumer PET fibers are then crimped using a stuffer-box crimper, not shown, as known in the art. In operation, the stuffer-box crimper receives a large number of semi-molten polymer fibers between a pair of smooth metal nip rolls and forces the fibers into a box or container having fixed dimensions and a variable resistance flapper device on the output opening. It is possible to increase the number of crimps per inch in the fibers by increasing the resistance of the flapper device of the output from the stuffer box. In short, greater resistance on the flapper device results in a higher number of crimps per inch on the fibers coming out of the stuffer-box. The post-consumer PET fiber 150 used in the present invention will normally have crimping in a range of about 1.0 to about 3.0 crimps per inch, with a value of 2.0 crimps per inch being preferred. The crimped PET fibers 150 are cut to lengths ranging from about 5.75 inches to about 6.25 inches, with a length of about 6.0 inches being preferred.

The post-consumer PET fibers 150 used in the present invention have been tested for resistance to compression. The testing procedure begins by first carding

an 8.0 to 10.0 gram sample of fibers which are of 2.5 inches maximum length. The carded fibers are then weighed out into a 3.00 ± 0.05 gram sample using an analytical balance. The 3.0 gram carded sample is then placed into the 3.0 inch diameter compression cup of an Instron resistance to compression tester. The compression cup is then sealed and air pressure applied to the fiber sample. The testing apparatus then computes a resistance to compression for the fiber sample in pounds. The crimped, post-consumer PET fibers used as a filler material in the present invention exhibited resistance to compression values ranging from about 4.5 pounds to about 6.0 pounds, with an average value of about 5.2 pounds. This value may also be converted into a resistance to compression value expressed pounds per square inch (psi) per gram of fiber. Thus, for a fiber sample with an average resistance to compression value of about 5.2 pounds, it is possible to calculate a value of about 0.245 psi/gram of fiber.

An additional measure of crimped PET fiber resiliency may be obtained by studying the ability of an amount of filler material to recover its original thickness after the application and removal of a particular load. In one such test, one (1.0) pound of crimped PET fiber loose filler is placed in a circular container having a 6.0 inch diameter and its thickness is measured. A compressive load of 0.5 psi is then applied evenly across the top surface of the loose filler for a period of 5.0 minutes. After the compressive load is removed, the thickness of the loose filler is measured again. A

percent recovery is then computed by dividing the thickness after compression by the original thickness and multiplying by 100%. For the crimped, post-consumer PET fibers used as a filler material in the present invention, it was determined that the loose filler had a percent recovery value ranging from about 95% to about 97% of its original thickness.

Referring now to Figure 4, a block diagram illustrates, by way of example only, the various steps of a manufacturing process 400 which may be followed to construct an erosion control blanket in accordance with the present invention. In one embodiment, post-consumer plastic materials such as soda bottles and containers are collected and sorted 405 according to polymer types (e.g., polystyrene, polyethylene terephthalate, polybutylene terephthalate, polyethylene, polypropylene, and so forth). These containers are then mechanically shredded 410 and cleaned 415 with high temperature steam to produce post-consumer scrap polymer which is suitable for reprocessing. A fiber manufacturer may then purchase scrap polymer of a particular type, such as PET, pelletize 420 the scrap polymer, melt the polymer 425 in an extruder, and melt spin 430 fibers from the polymer. These fibers may then be crimped 435 using a stuffer-box crimper as described hereinabove and cut 440 to a particular length to produce a crimped loose fiber filler material. An erosion control blanket may then be produced by providing top and bottom sheets of netting material 445, randomly

dispersing 450 the cut, crimped polymer fibers between the top and the bottom sheet, and then stitching 455 the top and bottom sheets together. Once the top and bottom sheets are fastened or stitched together and the loose fiber fill material is secured, it is possible to roll the generally rectangular blankets up into smaller, cylindrical bundles for shipping and handling.

It is thus believed that the operation and construction of the present invention will be apparent from the foregoing description of the preferred embodiments. While the erosion control blanket materials, configurations and designs as shown are described as being preferred, it will be obvious a person of ordinary skill in the art that various changes and modifications may be made therein without departing from the spirit and scope of the invention, as defined in the following claims. Therefore, the spirit and the scope of the appended claims should not be limited to the description of the preferred embodiments contained herein.

WHAT IS CLAIMED IS:

1. A erosion control blanket comprising:
 - a top sheet of a netting material;
 - a bottom sheet of a netting material;
 - a synthetic filler material being disposed between said top sheet and said bottom sheet; and
 - wherein said synthetic filler material further comprises a plurality of crimped polymer fibers which are arranged to form a three-dimensional matrix.
2. The erosion control blanket of claim 1, wherein said synthetic filler material is a polyester.
3. The erosion control blanket of claim 2, wherein said polyester is polyethylene terephthalate (PET).
4. The erosion control blanket of claim 2, wherein said polyester is substantially post-consumer, recycled polyethylene terephthalate (PET).

5. The erosion control blanket of claim 4, wherein said recycled polyethylene terephthalate (PET) is substantially of green soda bottle material.

6. The erosion control blanket of claim 1, wherein said synthetic filler material has a resistance to compression value of about 0.210 to about 0.285 psi/gram of fiber.

7. The erosion control blanket of claim 1, wherein said synthetic filler material has a percent recovery value of at least 90% following the application of a 0.5 psi compressive load for a period of 5.0 minutes.

8. The erosion control blanket of claim 1, wherein said crimped polymer fibers have about 1.0 to about 3.0 crimps per inch.

9. The erosion control blanket of claim 1, wherein said crimped polymer fibers contain additives to increase resistance to ultraviolet (UV) radiation.

10. A method of making an erosion control blanket, said method comprising the steps of:

providing post-consumer polymer material;

cleaning said post consumer polymer material;
forming the cleaned post-consumer polymer material into polymer fibers;
crimping the polymer fibers at intervals along their length to form crimped
polymer fibers;
cutting the crimped polymer fibers to form a loose fiber filler;
providing top and bottom sheet netting adapted for receiving said loose
fiber filler therebetween; and
securing the loose fiber filler between said top and bottom sheet netting
to form said erosion control blanket.

11. The method of claim 10, wherein said post-consumer polymer material is
a polyester.

12. The method of claim 11, wherein said polyester is polyethylene
terephthalate.

13. The method of claim 12, wherein said polyethylene terephthalate is
substantially of green soda bottle material.

14. The method of claim 10, wherein the crimping step is carried out using a stuffer-box crimper.

15. The method of claim 10, wherein the fibers are crimped with about 1.0 to about 3.0 crimps per inch.

16. The method of claim 10, wherein the fibers are cut at a length of about 5.75 inches to about 6.25 inches.

17. The method of claim 10, wherein the step of forming the cleaned post-consumer polymer material into polymer fibers further comprises the steps of:

pelletizing said cleaned post-consumer polymer material to form polymer pellets;

extruding said polymer pellets as a polymer melt; and

melt spinning said polymer melt to form polymer fibers.

18. An erosion control blanket constructed according to the method of claim 10.

ABSTRACT OF THE INVENTION

A durable erosion control blanket featuring a novel synthetic fiber filler is disclosed. The erosion control blanket of the present invention addresses the need for a particularly resilient erosion control blanket through the use of a post-consumer, crimped, polyester fiber filler material. In one embodiment, the post-consumer fiber material is of polyethylene terephthalate (PET) readily available in post-consumer form from the recycling of soda bottles. In short, a preferred filler material for the blanket of the present invention would utilize recycled soda bottle material which has been converted into a crimped, highly-resilient fibrous filler. It is, thus, possible to achieve the desired physical and mechanical properties in the erosion control blanket of the present invention while conserving natural resources to some extent by using a readily available post-consumer polymer material.




FIG. 1




FIG. 2





FIG. 3



**RULES 63 AND 67 (37 C.F.R. 1.63 and 1.67)
DECLARATION AND POWER OF ATTORNEY**

FOR UTILITY/DESIGN/CIP/PCT NATIONAL APPLICATIONS

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; and

I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: , the specification of which: (mark only one)

- X (a) is attached hereto.
— (b) was filed on _ as Application Serial No. _ and was amended on _____ (if applicable)
— (c) was filed as PCT International Application No. PCT/_____ on _____ and was amended on _____ (if applicable).
— (d) was filed on _____ as Application Serial No. _ and was issued a Notice of Allowance on _____.
— (e) was filed on _____ and bearing attorney docket number _____

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended by any amendment referred to above or as allowed as indicated above.

I acknowledge the duty to disclose all information known to me to be material to the patentability of this application as defined in 37 CFR § 1.56. If this is a continuation-in-part (CIP) application, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose to the Office all information known to me to be material to patentability of the application as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

I hereby claim foreign priority benefits under 35 U.S.C. § 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate filed by me or my assignee disclosing the subject matter claimed in this application and having a filing date (1) before that of the application on which my priority is claimed or, (2) if no priority is claimed, before the filing date of this application:

PRIOR FOREIGN PATENTS

<u>Number</u>	<u>Country</u>	<u>Month/Day/Year</u> <u>Filed</u>	<u>Date first</u> <u>laid-open or</u> <u>Published</u>	<u>Date</u> <u>patented or</u> <u>Granted</u>	<u>Priority Claimed</u> <u>Yes</u> <u>No</u>
NONE					

I hereby claim the benefit under 35 U.S.C. § 120/365 of any United States application(s) listed below and PCT international applications listed above or below:

PRIOR U.S. OR PCT APPLICATIONS

Application No. (series code/serial no.) Month/Day/Year Filed Status(pending, abandoned, patented)

NONE

I hereby appoint:

TIMOTHY G ACKERMANN, Reg. No. 44,493	GERALD H. GLANZMAN, Reg. No. 25,035	DANIEL G. NGUYEN, Reg. No. 42,933
THOMAS E ANDERSON, Reg. No. 37,063	J. KEVIN GRAY, Reg. No. 37,141	SPENCER C. PATTERSON, Reg. No. 43,849
BENJAMIN J BAI, Reg. No. 43,481	STEVEN R. GREENFIELD, Reg. No. 38,166	RUSSELL N. RIPPAMONTI, Reg. No. 39,521
MICHAEL J BLANKSTEIN, Reg. No. 37,097	JOSHUA A. GRISWOLD, Reg. No. 46,310	ROSS T. ROBINSON, Reg. No. 47,031
MARY JO BOLDINGH, Reg. No. 34,713	J. PAT HEPTIG, Reg. No. 40,643	STEPHEN G. RUDISILL, Reg. No. 20,087
MARGARET A. BOULWARE, Reg. No. 28,708	SHARON A. ISRAEL, Reg. No. 41,867	HOLLY L. RUDNICK, Reg. No. 43,065
ARTHUR J BRADY, Reg. No. 42,356	JOHN R. KIRK JR., Reg. No. 24,477	J.L. JENNIE SALAZAR, Reg. No. 45,065
MATTHEW O BRADY, Reg. No. 44,554	PAUL R. KITCH, Reg. No. 38,206	KEITH W. SAUNDERS, Reg. No. 41,462
DANIEL J. BURNHAM, Reg. No. 39,618	TIMOTHY M. KOWALSKI, Reg. No. 44,192	JERRY R. SELINGER, Reg. No. 26,582
THOMAS L. CANTRELL, Reg. No. 20,849	JAMES F. LEA III, Reg. No. 41,143	GARY B. SOLOMON, Reg. No. 44,347
RONALD B. COOLLEY, Reg. No. 27,187	HSIN-WEI LUANG, Reg. No. 44,213	WAYNE O. STACY, Reg. No. 45,125
THOMAS L. CRISMAN, Reg. No. 24,846	ROBERT W. MASON, Reg. No. 42,848	STEVE Z. SZCZEPANSKI, Reg. No. 27,957
STUART D. DWORK, Reg. No. 31,103	ROGER L. MAXWELL, Reg. No. 31,855	ANDRE M. SZUWALSKI, Reg. No. 35,701
WILLIAM F. ESSER, Reg. No. 38,053	ROBERT A. McFALL, Reg. No. 28,968	ALAN R. THIELE, Reg. No. 30,694
ROGER J. FRENCH, Reg. No. 27,786	STEVEN T. McDONALD, Reg. No. 45,999	TAMSEN VALOIR, Reg. No. 41,417
JANET M. GARETTO, Reg. No. 42,568	LISA H. MEYERHOFF, Reg. No. 36,869	RAYMOND VAN DYKE, Reg. No. 34,746
JOHN C. GATZ, Reg. No. 41,774	STANLEY R. MOORE, Reg. No. 26,958	BRIAN D. WALKER, Reg. No. 37,751
RUSSELL J. GENET, Reg. No. 42,571	RICHARD J. MOURA, Reg. No. 34,883	GERALD T. WELCH, Reg. No. 30,332
	MARK V. MULLER, Reg. No. 37,509	HAROLD N. WELLS, Reg. No. 26,044
	P. WESTON MUSSELMAN JR, Reg. No. 31,644	WILLIAM D. WIESE, Reg. No. 45,217


all of the firm of **JENKENS & GILCHRIST, a Professional Corporation**, 1445 Ross Avenue, Suite 3200, Dallas, Texas 75202-2799, as my attorneys and/or agents, with full power of substitution and revocation, to prosecute this application, provisionals thereof, continuations, continuations-in-part, divisionals, appeals, reissues, substitutions, and extensions thereof and to transact all business in the United States Patent and Trademark Office connected therewith, to appoint any individuals under an associate power of attorney and to file and prosecute any international patent application filed thereon before any international authorities, and I hereby authorize them to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/organization who/which first sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct them in writing to the contrary.

Please address all correspondence and direct all telephone calls to:

Stanley R. Moore, Esq.
Jenkins & Gilchrist, P.C.
1445 Ross Avenue, Suite 3200
Dallas, Texas 75202-2799
214/855-4500
214/855-4300 (fax)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

NAMED INVENTOR(S)

	Gerald Davis Bohannon, Jr. Full Name	 Inventor's Signature	8/25/00 Date
1	No. 8 Old Stage Trail Lake Wylie, South Carolina 29710 Residence (city, state, country)		
	Citizenship USA No. 8 Old Stage Trail Lake Wylie, South Carolina 29710 Post Office Address (include zip code)		

(FOR ADDITIONAL INVENTORS, check here __ and add additional sheet for inventor information regarding signature, name, date, citizenship, residence and address)

005680-9064900